



Waterproofing XCEM ALPHAFLOOR® Flooring

Products required

- MAXJOINT ELASTIC or MAXJOINT ELASTIC EXPRESS.
- MAXSEAL FLEX or MAXSEALFLEX-M or MAXSEAL TRAFFIC
- MAXMESH
- MAXREST PASSIVE

Method

1. Prepare area to be treated by removing any loose materials, ensuring a clean and sound surface. If surface previously painted or waterproofed, materials must be removed.
2. Wet tongue & groove joints between each floor sheet, fill with MAXJOINT ELASTIC or MAXJOINT ELASTIC EXPRESS, allow to cure over-night.
3. Wet the surfaces and brush apply MAXSEAL FLEX, MAXSEAL FLEX-M or MAXSEAL TRAFFIC onto each tongue & groove joint area according to product specifications. Embed 50mm wide MAXMESH into the first coat of MAXSEAL FLEX, MAXSEAL FLEX M or MAXSEAL TRAFFIC.
4. Wet the surfaces and brush apply MAXSEAL FLEX, MAXSEAL FLEX-M or MAXSEAL TRAFFIC for 100mm onto the wall and abutting floor sheet, according to product specifications. Embed 200mm wide MAXMESH into the first coat of MAXSEAL FLEX, MAXSEAL FLEX M or MAXSEAL TRAFFIC. Ensure the MAXMESH is moulded into the corner at floor/wall joint.
5. Allow these joints to cure over-night.
6. Wet surface and brush apply 1st coat of MAXSEAL FLEX, MAXSEAL FLEX-M or MAXSEAL TRAFFIC at the rate of 1kg/m² over entire surface.
7. Allow 1st coat to set overnight.
8. Wet surface and brush apply 2nd coat of MAXSEAL FLEX, MAXSEAL FLEX-M or MAXSEAL TRAFFIC over entire area at the rate of kg/m² according to product specifications.
9. Leave for 5 days minimum prior to application of other finishes or processes e.g., painting, tiling, or cladding.

Caution:

We do not recommend the use of MAXSEAL FLEX, MAXSEAL FLEX-M OR MAXSEAL TRAFFIC directly onto zinc or zinc coated surfaces, treat these surfaces using MAXREST PASSIVE. as per TDS prior to coating.

For tiling we recommend the use of:

- Maxkola Flex, a flexible waterproof tile adhesive
- Maxjoint Flex, a waterproof flexible Tile Grout

All Drizoro Products are warranted for 10 Years.

© Scientific Waterproofing Products Pty Ltd. ABN: 155 659 948 All rights reserved.
Address: Unit 4/92 Bryant Street, Padstow, NSW 2211, Australia
Tel: +61 2 9771 0011
Email: admin@swppl.com.au
<http://swppl.com.au/>
National Hotline: 1300 303 301

Don't just waterproof it... DRIZORO it!
Visit: www.swppl.com.au